



HGS (INDIA) LIMITED



HGT SERIES OF GEOPHONE TESTERS A solution for every QC problem

HGT-1L – 3 Channels Geophone Test Option



- Versatile Quality-Control System
- Geophone Test – 3 Channels at Once
- Hydrophone Test Option Available
- System includes: HGT-1L unit, GeoTest Cable, Power & Ethernet Cables

158, Sector-4, IMT Manesar, Gurgaon-122050 Haryana INDIA
Tel: +91 (0124) 4681800, Fax: +91 (0124) 4681845
Email: sales@hgsindia.com



HGS (INDIA) LIMITED



SPECIFICATIONS of HGT-1L*	
Natural Frequency	
Range	1 to 150 Hz
Accuracy	+/- 1% (+/- 0.5 Hz below 7 Hz) (+/- 2% above 15 Hz)
Display Resolution	0.01 Hz
Coil Resistance	
Range	20 to 99,999 Ohm
Accuracy	+/- 1 % or 1 Ohm whichever is greater
Display Resolution	0.1 Ohm
Damping	
Range	0 to 0.85
Accuracy	+/- 1 % of measured value
Display Resolution	0.001
Sensitivity	
Range	0 to 999 V/m/s
Accuracy	+/- 2 %
Display Resolution	0.1V/m/s
Harmonic Distortion	
Range	0-20%
Accuracy	+/- 10% of measured value or +/- 0.01 % whichever is greater
Display Resolution	0.01 %
Impedance	
Range	20 to 99,999 Ohm
Accuracy	+/- 1 % or 1 Ohm whichever is greater
Display Resolution	0.1 Ohm
Physical Characteristics	
Dimensions	14.0 x 5.5 x 3 in. (356 x 140 x 76 mm)
Weight	3.4 lbs (1.55 kg)



HGS (INDIA) LIMITED



Environmental Specifications	
Operating Temperature Range	-20 to +50°C
Storage Temperature Range	-20 to +40°C
Humidity	0 – 80% RH
Housing Standard	IP-65

**Measurement Standard – Measured at +20°C*

Version 1.1