





5/8-24 UNEF

Shell : Aluminium Alloy, Olive Drab Chromate Over Cadmium Plated
 Insert : Neoprene
 Contacts : Copper Alloy Solder, Silver Plated
 Rated dc working voltage : ≥ 700 V
 Rated current : ≥ 13 A
 Operating temperature : -55°C to 125°C
 Insulation resistance : ≥ 5000 M Ω at 500 V dc
 Wire termination : Solder type

Note : All dimensions are approximate.

REV	DESCRIPTION	APD	DATE
TREATMENT			
ALL DIMENSIONS IN MM			
MATERIAL			
UNLESS OTHERWISE SPECIFIED			
NOM.DIM	...6	>6...30	>30...100
TOL.	± 0.1	0.2	0.3
BREAK EDGES	R.MAX. 0.3	ANGLES TOL	$\pm 0.15^{\circ}$
FINISH			
SCALE	N.T.S.		
CHD		10 ⁰⁹ / ₂₁	
REW		10 ⁰⁹ / ₂₁	
APD		10 ⁰⁹ / ₂₁	
HGS			
HGS (INDIA) LIMITED			
158, SECTOR-4, IMT MANESAR GURUGRAM-122 050			
TITLE	RECEPTACLE TYPE 3 PIN M PM CONN.		
REF.NO.	(CT2-10SL-3PS)		
DRG. NO.	REV.	PAGE	
MK000897		1 OF 1	