



Shell : Aluminium Alloy, Olive Drab Chromate Over Cadmium Plated
 Insert : Neoprene
 Contacts : Copper Alloy Solder, Silver Plated
 Rated dc working voltage : ≥ 700 V
 Rated current : ≥ 13 A
 Operating temperature : -55°C to 125°C
 Insulation resistance : ≥ 5000 M Ω at 500 V dc
 Wire termination : Solder type

Note : All dimensions are approximate.

REV	DESCRIPTION	APD	DATE
TREATMENT			
ALL DIMENSIONS IN MM			
MATERIAL			
UNLESS OTHERWISE SPECIFIED			
NOM.DIM	...6	>6...30	>30...100
TOL. \pm	0.1	0.2	0.3
BREAK EDGES	R.MAX. 0.3	ANGLES TOL	$\pm 0.15^{\circ}$
FINISH			
SCALE N.T.S.			
CHD	10/09/21		
REW	10/09/21		
APD	10/09/21		
HGS HGS (INDIA) LIMITED 158, SECTOR-4, IMT MANESAR GURUGRAM-122 050			
TITLE 3 PIN F STRAIGHT CABLE CONN. WITH INTEGRAL CABLE CLAMP			
REF.NO. (CT6E10SL-3SS)			
DRG. NO.		REV.	PAGE
MK000898			1 OF 1